

/ Thickness

From Nature
Used for wall surfaces

100%
WILDSTONE

云杉石

任何现代的涂料，合成材料都黯然失色
在灰泥 (Stucco) 面前

零污染，节能控温

100% 纯天然，零 VOC

是一种黏土涂层组成的，具有颜值高

它是从天然采石场中提取的生物黏土

与传统合成涂料不同

他们都取自大自然拥有的颜色

均使用赭石颜料，亦即无机矿物颜料

目前全系列灰泥材料

支持环保事业

正如我们一如既往的

We will continue as always
Support the
environmental protection cause



为什么是地球的颜色？

VAN LIME SERIES



阅石留痕 / 系列

In Natural
We Trust

天然矿物石材 最好看！

每一种纹理,都是自然的语言
也是空间的呼吸节奏

Every texture is a natural language
It is also the breathing rhythm of space



天然矿物
多孔结构,稀释调节湿度

Natural Mineral

Porous structure, diluted to regulate humidity



矿物基材
天然成分,安全无毒

Mineral substrate

Natural ingredients, safe and non-toxic



抗菌防霉
抑制霉菌滋生,安心耐用

Antibacterial

Inhibit mold growth, safe and durable



细致触感
质感温润,温和亲肤

Detailed tactile sensation

Warm texture, gentle and skin friendly



擦色



肌理



施工视频

Construction video

Mineral Texture, Natural Living.





29°釉质柔光光泽，温润石质

29 ° enamel soft gloss

Warm and moist stone

vanlei万磊®

色系划分：提供2种基料，一个为搭配预拌色系的色浆系统
另一个是擦色系统。统一使用万磊无机色浆调色。

Provide two types of base materials, pre mixed color system and wiping system
Unified use of Vanlei inorganic color paste for color matching



云杉石 - 擦色

YSS基料 - RL+M10(20g)



云杉石 - 肌理

YSS - 基料

色卡颜色与实际材料颜色有少许差异为正常现象



哑光磨砂质地，不易显脏耐抚触

Matte matte texture
not easily dirty and resistant to touch

vanlei万磊®

擦色 / Antiquing



云杉石

YSS基料 - RL+M01(100g)



云杉石

YSS基料 - RL+M15(20g)



云杉石

YSS基料 - RL+M12(20g)



云杉石

YSS基料 - RL+6276(10g)



云杉石

YSS基料 - RL+M10(20g)



云杉石

YSS基料 - RL+6273(30g)

It is normal for the color card color to differ slightly from the actual material color



防水防潮出色：拥有良好的防水性能

Excellent waterproof and moisture-proof performance
Has good waterproof performance

vanlei万磊®

擦色 / Antiquing



云杉石

YSS基料 - RL+M03(100g)



云杉石

YSS基料 - RL+M32(10g)



云杉石

YSS基料 - RL+6274(10g)



云杉石

YSS基料 - RL+M38(5g)



云杉石

YSS基料 - RL+M31(10g)



云杉石

YSS基料 - RL+M50(5g)

色卡颜色与实际材料颜色有少许差异为正常现象



透亮感强, 呈现天然矿物折射光晕

Strong transparency,
presenting a natural mineral refraction halo

vanlei万磊®

肌理

Texture



云杉石

YSS - M29(100g)



云杉石

YSS - M08(100g)



云杉石

YSS - M18(100g)



云杉石

YSS - 6281(100g)

29°柔光

29° soft light
The most natural
liquid stone

最天然的液态石材

颜值高, 100%纯天然, 零VOC, 零污染, 节能控温

It is normal for the color card color to differ slightly from the actual material color

CN.	
产品综述 /	这是一种回归本源的命名
主要成分 /	充分调配的熟石灰，精细大理石粉，无机颜 / 填料，纳米碳酸钙粉
准备工具 /	批刀 -YG114, 铲刀 -YG075, 海藻绵滚筒 -YG163, 天然海藻滚筒 -YG063, 羊毛滚筒 -YG090, 碳晶纹小滚筒刷 -YG135, 打磨机 -YG162
色浆混合 /	使用天然石料颜色，无机色浆调色
适用范围 /	适用于的室内墙面，内部客厅墙面等家居空间，或商业室内空间亦可
配套产品 /	万磊渗透底漆 + 万磊云杉石 + 万磊极致哑光罩面
基面处理 /	参考环境条件温度 -25°C, 湿度 ≤ 60 ①基层应平整，干净无油污，空鼓，并具有较好的强度，方可施工 ②旧墙翻新：铲平基层，清除松动的表层部分，清洁粉尘油污等杂质后方可施工 ③基材必须完全干燥无尘和盐渍。如有必要，使用特定产品重新铺设或加固表面
参考用量 /	平面擦色款： 1.8-2kg/ m² /2 遍 岩石款： 3.5-4.5kg/ m² /2 遍，根据肌理的质感厚薄
净含量 /	20kg

EN.	
Product Overview /	The name "Wildstone" in Vanlei is derived from the native landscape of the countryside, without excessive modification of the land, grassland, and exposed rock layers, which is the closest visual impression to the initial state of nature It emphasizes' nature that has not been designed ' The undulations left by the wind blowing through the fields and the traces of rainwater seeping into the soil layers are transformed into the language of wall texture The material adopts an environmentally friendly formula system to reduce the dependence on high polluting resins, ensuring the stability and breathability of the wall during long-term use In Vanlei, as a liquid stone, it has a delicate texture, presenting the rough touch and warm luster of natural stones, and possessing high weather resistance and plasticity Fieldstone does not emphasize decoration, but exists as the base color of the space Suitable for residential living rooms and rural homestays, it brings the space back to a quiet and unexpressed state This is a naming that returns to the origin
Main ingredients /	Fully blended hydrated lime, fine marble powder, inorganic pigments/fillers, nano calcium carbonate powder
Tool /	Batch knife - YG114, shovel knife - YG075, seaweed sponge roller - YG163, natural seaweed roller - YG063, wool roller - YG090,Carbon crystal pattern small roller brush - YG135, polishing machine - YG162
Color Mixing /	Use natural stone color and inorganic color paste for color matching
Application /	Suitable for indoor large walls, interior living room walls, and other home spaces, as well as commercial indoor spaces
Matching products /	Vanlei Penetrating Primer + Vanlei Wildstone + Vanlei Ultimate matte finish
Coverage rate /	Color coating: 1.8-2kg/ m² /2 layers Texture: 3.5-4.5kg/ m² /2 layers, depending on the thickness of the texture
Net Content /	20kg

佛山市南海万磊建筑涂料有限公司

Foshan City Nanhai Wanlei Building Paint CO., LTD



广东生产基地（代码FS）

佛山市南海区狮山镇松岗万石管理区
象头岗万石村工业路1、2、5号

广州分公司

广州市荔湾区羊城装饰材料市场172号

广西生产基地（代码QT）

广西壮族自治区贵港市覃塘区产业园甘化园区

南宁分公司

广西壮族自治区南宁市兴宁区快环建材市场

△ 注意

公司根据产品技术和发展需要，有权对产品配方进行更新升级，而不对外另行公布，请以最新样板册颜色为准，不便之处，敬请原谅！

4000-147-187 www.fswanlei.com



辊涂万磊金装白色/透明底漆(1/2遍)
兑水15-20%使用
Roller coated Vanlei Gold white/transparent primer
(1/2 coat) Mix 15-20% water for use



施工稠度须根据气温调整加水比例
满批2遍
Adjust the water addition ratio according to the
temperature during construction Batch 2 times



彻底干燥后，进行打磨

打磨工序：
180细打—320目精磨—1000目抛光(可选)

After thorough drying, polish

Polishing process:
180 fine grinding -320 mesh precision grinding
~1000 mesh polishing (optional)



罩面层(推荐使用无缝罩面),均匀辊涂
两遍 (加水10-15%)

Cover layer (recommended to use seamless
cover).Apply evenly twice with a roller add
10-15% water



彻底干燥后,用海藻滚筒擦色,可选择极致
哑光罩面

After thorough drying, use a seaweed roller to wipe
the color, and choose the ultimate matte finish

肌理施工方法请扫码观看

Please scan the code to view the texture
construction method